



PARLASTIC® HIGH PERFORMANCE SEALANT

Product Overview: PARLASTIC, manufactured at the PARR facility, is a premium, non-sag sealant that is formulated to provide excellent adhesion to glass, aluminum, brick, and most other construction materials. In its cured state, PARLASTIC exhibits desirable polymeric characteristics, such as elongation, compression, water-resistance, and low temperature flexibility.

Product Uses: PARLASTIC is primarily used in construction work for indoor and outdoor sealing applications such as: siding, channel glazing, porcelain panel construction, and joint sealing. It is also used in the manufacture of RV's, manufactured houses, and vehicles. When used in vertical and horizontal joints, PARLASTIC can be used to seal openings up to 1/2" x 1/2".

Technical Information:

Raw Material Base.....	Synthetic Polymer	Solids by Weight.....	69 – 76%
VOC.....	254 g/l	Flash Point.....	40°F
Color.....	Aluminum	Tack Free Time (77°F).....	30 min.
Specific Gravity.....	0.89 – 0.94	Shelf Life.....	One Year
Elongation (ASTM D412).....	500%	Manufactured State.....	Liquid
Tensile Strength.....	30 psi	Odor.....	Aromatic Pre-cure, None Post-cure
Viscosity, Melt Flow Index.....	40 – 45 sec.	Service Temperature.....	-20 – 160°F
Water Resistance.....	Excellent	Full Cure Time.....	24 – 72 Hours

Application Information: Ensure surfaces to be sealed are clean, dry, and free of oil and moisture. Exercise care during application to prevent air or contaminant entrapment. For best results, apply in a smooth bead and allow to level. Do not handle, move, or pack for one hour until a surface film has formed. If necessary, clean tools and equipment with mineral spirits.

Packaging & Handling: Do not open until ready for use in order to maximize shelf life. Store at 60° – 80°F. Read all labeling before use.

Safety Instructions: WARNING! This product contains toluene, a solvent flammable in both liquid and vaporous states. Keep away from heat, spark, and open flame. Disconnect all gas and electrical appliances near work area. Use in a well ventilated area. Overexposure to vapors may cause dizziness, headache, and unconsciousness. Wear gloves and eye protection. Liquid product is an eye and skin irritant, and is harmful if swallowed. Consult Material Safety Data Sheet for further information.

Contact Us: For more information regarding this product and others, please contact us at:

Edge Adhesives
3200 County Rd. 6 East
Elkhart, IN 46514
www.edgeadhesives.com

Toll Free: 1-866-476-PARR
Phone: 1-574-264-9614
Fax: 1-574- 262-9201

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Edge Adhesives control are such that Edge Adhesives assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.

EDGE ADHESIVES BRANDS



PARLASTIC