



PTI 757 BUTYL SEALANT

Product Overview: PTI 757, manufactured at the PARR facility, is a skinning sealant formulated to meet Federal Specification TT-S-001657, Canadian Specification 19 GPN, AAMA Specification 808.3, and ASTM C-1085. This product does not lose flexibility, elongation, or adhesion even after prolonged exposure to extreme temperatures and ultraviolet light. PTI 757 also features excellent slump resistance.

Product Uses: PTI 757 is recommended for use in the following applications: metal-to-metal panel seals, perimeter seals around doors, windows, and masonry intersections; and as bedding for mullions, framed openings, and coping areas. It can also be used to seal curtain walls, end dams, and splice joints. In addition, PTI 757 can be used for glass glazing, heel and toe beading, and complete channel bedding.

Technical Information:

Raw Material Base.....Synthetic Polymer	Solids by Weight.....76-80%
Weight per Gallon.....10 – 11 lb.	Service Temp. Range.....-45°F – 210°F
Color.....Black, Grey, Neutral, White, Bronze	Application Temp. Range.....20°F – 120°F
VOC.....248 g/L	Melt Flow Index Time.....40 – 70 sec.
Elongation (ASTM D412).....Cured, 450%	Tack Free Time.....24 hrs. max
Odor.....Neutral	Full Cure Time.....14 days
Slump......1875" max	Shelf Life.....One Year
QUV Exp., 250 hrs.No Effect	Physical State.....Caulk

Application Information: Ensure surfaces to be sealed are clean, dry, and free of oil and moisture. Exercise care during application to prevent air or contaminant entrapment. PTI 757 is most commonly applied by pumping, either by caulking gun or power gun. It can also be applied by trowel or stiff brush. For best results, apply in a smooth bead and allow to level. Do not handle, move, or pack for one hour until a surface film has formed. If necessary, clean tools and equipment with mineral spirits.

Packaging & Handling: Do not open until ready for use in order to maximize shelf life. Store at 60° – 80°F. Read all labeling before use. PTI 757 is available in cartridges, five gallon pails, and fifty-five gallon drums.

Safety Instructions: CAUTION! This product contains mineral spirits, a combustible organic solvent. Keep away from heat, spark, and open flame. Avoid overexposure to vapors, as they may cause dizziness, nausea, and unconsciousness. Avoid exposure to skin and eyes. Consult Material Safety Data Sheet for further information.

Contact Us: For more information regarding this product and others, please contact us at:

Edge Adhesives
3200 County Rd. 6 East
Elkhart, IN 46514
www.edgeadhesives.com

Toll Free: 1-866-476-PARR
Phone: 1-574-264-9614
Fax: 1-574- 262-9201

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Edge Adhesives control are such that Edge Adhesives assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.

EDGE ADHESIVES BRANDS



PLIOSEAL



PTI 757