

Edge Adhesives 7206 Black (PARR MP Sealant) Butyl Sealant Tape

PRODUCT DESCRIPTION

Edge Adhesives 7206 is a premium butyl rubber-based sealant tape designed to prevent water and air penetration. Black in color, 7206 combines ease-of-use with superior adhesion to most surfaces. Manufactured in easy-to-use rolls, 7206 is perfect for the appliance industry. Standard sizes are 1/8" x 1" x 50' and 1/8" x 2" x 40'. Custom sizes are available.

DIRECTIONS FOR USE

EP 7206 is designed for use in the appliance industry to seal cabinets and prevent the intrusion of water and air around pipes and wires. Edge Adhesives 7206 material is extruded onto removable release paper backing to facilitate handling. For most efficient usage, it is recommended that the material be pressed onto one surface, stripped of its paper backing, and then brought into contact with the second surface. All surfaces involved should be clean and dry. For best adhesion to wood and porous surfaces, prime the designated area before applying this product.

STORAGE AND HANDLING

It is suggested that the material be stored in a cool <80°F (27°C), dry area in the original sealed containers. No special handling is required.

SAFETY INSTRUCTIONS

No special requirements are needed. Safety Data Sheets are supplied upon request.

FEATURES

- ▶ Easy compressibility. Non-sagging and non-oxidizing.
- ▶ Forms seals in junctions of complex geometry. Adheres well to all surfaces.
- ▶ Composition is 99% solids, non-hazardous, and contains no solvents.
- ▶ Easy to use and can apply by hand.

SPECIFICATIONS

PROPERTY

Raw Material Base:
Cone Penetration (@ 77°F, 300g):
Specific Gravity:
Color:
Solids by Weight:
Elongation:
Tensile Strength
Shelf Life:
Odor:
Service Temperature Range:

VALUE

Synthetic Polymer
8.0 mm – 8.5 mm
1.25 – 1.35
Black
100% solids
900 – 1000%
14 – 18 psi
1 year
Neutral
-20°F (-28°C) – 180°F (82°C)

The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all your requirements.