

Edge Adhesives 7216 and 7217 (PARR GP) Green and White Butyl Floral Tapes

PRODUCT DESCRIPTION

Edge Adhesives 7216 and Edge Adhesives 7217 are premium butyl rubber based adhesive tapes specifically designed for the floral market. Available in green as 7216 and white as 7217, these butyl floral tapes combine ease-of-use with superior adhesion to most surfaces. Manufactured in easy-to-use rolls, EP 7216 and EP 7217 are perfect for anchoring floral arrangements, glass, plastic, candles, and figurines. This tape is available in 1/8" x 1/2" x 25'. Custom sizes are available.

DIRECTIONS FOR USE

Edge Adhesives 7216 and 7217 are designed for use in the floral industry. It can also be used for roof seam sealing, RV manufacturing, construction of curtain wall panels, channel glazing, and duct sealing for air conditioning, windows, and doors. EP 7216 and EP 7217 materials are extruded onto removable release paper backing to facilitate handling. For most efficient usage, it is recommended that the material be pressed onto one surface, stripped of its paper backing, and then brought into contact with the second surface. When using to seal applications involving fasteners, position on the entry side to prevent the penetration of contaminants through fastener holes.

STORAGE AND HANDLING

It is suggested that the material be stored in a cool <80°F (27°C), dry area in the original sealed containers. No special handling is required.

SAFETY INSTRUCTIONS

No special requirements are needed. Safety Data Sheets are supplied upon request.

FEATURES

- ▶ Easy compressibility. Non-sagging and non-oxidizing.
- ▶ Forms seals in junctions of complex geometry. Adheres well to all surfaces.
- ▶ Composition is 99% solids, non-hazardous, and contains no solvents.
- ▶ Easy to use and can apply by hand.

SPECIFICATIONS

PROPERTY

PROPERTY	VALUE
Raw Material Base:	Synthetic Polymer
Needle Penetration (@ 77°F):	8.5 mm – 9.5 mm
Specific Gravity:	1.6 – 1.7
Color:	Green (EP 7216), White (EP 7217)
Solids by Weight:	99% solids
Elongation (ASTM D142):	>1500%
Tensile Strength:	10 – 12 psi
Flash Point:	325°F
QUV Exposure:	Surface discoloration only
Water Absorption:	0.3% in distilled water for 24 hours
Odor:	Neutral
Shelf Life:	1 year
Service Temperature Range:	-40°F (-40°C) – 180°F (82°C)

The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all your requirements.